

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
18 December 2003 (18.12.2003)

PCT

(10) International Publication Number
WO 03/105439 A1

- (51) International Patent Classification⁷: **H04L 29/06**
- (21) International Application Number: **PCT/GB02/02648**
- (22) International Filing Date: **10 June 2002 (10.06.2002)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (71) Applicant (for all designated States except US): **CAPLIN SYSTEMS LIMITED** [GB/GB]; Mercury House, Triton Court, 14 Finsbury Square, London EC2A 1BR (GB).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **HAWLEY, Adam, Stanley, James** [GB/GB]; 141 The Manor Drive, Worcester Park, Surrey KT4 7LN (GB).
- (74) Agents: **WALASKI, Jan et al.**; Venner, Shipley & Co., 20 Little Britain, London EC1A 7DH (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **RESOURCE MANAGEMENT**



(57) Abstract: A method of load balancing for establishing persistent connections over the Internet, in which a client connects to a server and receives a list of servers capable of providing a service, together with status information indicating which of the servers are available, the number of users currently being served by each server and a priority grouping to which each server belongs. Based on the list, the client makes a decision as to the server that is to provide the service.

WO 03/105439 A1

Resource Management

Field of the Invention

The present invention relates to a method of resource management, wherein the resource to be managed comprises a plurality of servers for providing a service to a client. In particular, the present invention relates to a method of load balancing in which the server to be used to provide the service to the client is selected by the client.

Background

There are several known methods of load balancing, a technique which aims to ensure that clients requesting a service over the Internet receive the service reliably, while the load on the servers providing the service is evenly spread, so that no single server is overburdened. Conventionally, a client provides a URL address to log on to a web server which is associated with a particular service required by the client, for example viewing a website. Typically, for websites needing to handle a large volume of traffic, the URL is mapped to a number of servers arranged as a cluster, also known as a server farm. The server cluster is required to deal with all of the users requesting the service without overloading individual servers.

Typical Internet transactions involve each user making numerous HTTP (hypertext transfer protocol) requests during a single Internet session. Each request opens a connection between client and server. After the request is satisfied, for example by the provision of a web page in HTML (hypertext mark-up language) format, the connection is terminated. A subsequent request from the client restarts the connection process, so that each request is independent and can be routed to the most appropriate server, for example based on the number of users being served by the server. In general terms, in the case of an HTTP based service, the servers providing the service are identical from the user's point of view. Therefore, a reliable service can be provided to each user by spreading the user requests among the available servers in some predetermined manner.

Known load balancing methods include the DNS round-robin algorithm, various software-based load balancing packages as well as switch-based applications.

However, in cases where it is important for a user to maintain a connection to a particular server, the above approaches are not suitable.

Summary of the Invention

According to the invention, there is provided a method of resource management, the resource comprising a plurality of servers, each of which is capable of providing a service to a client, the method comprising the steps of receiving a request for the service from the client; in response to said request, providing the client with information identifying each of the plurality of servers and selecting, at the client, one of the plurality of servers as the server to be used to provide the service to the client.

By permitting the client to select the server to be used, the client can achieve greater control over the load balancing process.

According to the invention there is further provided a client in a client/server system, comprising means for requesting a service from a server, means for receiving information in response to said request, said information identifying each of a plurality of servers which are configured to provide the service and means for selecting one of the plurality of servers as the server to be used to provide the service to the client.

According to the invention, there is also provided a server in a client/server system having a plurality of servers each configured to provide a service, comprising means for receiving a request for the service from a client and means for sending information to the client in response to said request, said information identifying each of the plurality of servers to the client.

The invention further provides a client/server system having a plurality of servers each configured to provide a service to a client, comprising means for

communicating information between the servers so that each of the plurality of servers maintains information relating to all of the servers, means for receiving a request for the service from a client and means for sending server information to the client in response to said request, said server information identifying each of the plurality of servers to the client.

Brief Description of the Drawings

Embodiments of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

- 10 Figure 1 illustrates an Internet connection scheme including a plurality of servers for providing a service to a client;
- Figure 2 is a schematic diagram illustrating how identity and status information is exchanged between servers;
- Figure 3 is a flow diagram illustrating the process of initial server selection; and
- 15 Figure 4 is a flow diagram illustrating the process of server selection in the event that a connection fails.

Detailed Description

Figure 1 illustrates a system on which the invention can be implemented in which a user uses browser software 1 running on a computer 2 to access any one of a number of server machines 3 – 5 via the Internet 6. The browser software 1, for example, Internet Explorer™ or Netscape Navigator™, is referred to herein as a client 1. The server machines 3 - 5, collectively referred to herein as a server farm 7, are configured to provide services, for example web pages, to the client 1. The server machines 3 - 5 are also referred to herein as data servers or simply servers.

Each of the plurality of server machines ServerA 3, ServerB 4 and ServerN 5 has a point to point connection 8 – 10 to each of the other servers in the farm 7.

- 30 It will be understood that each of the data servers 3 - 5 comprise conventional server computers which have the necessary hardware and operating system and application software to implement the functionality defined by the invention.

The domain name of each server 3 – 5 in the farm 7 maps to an Internet Protocol (IP) address, in a conventional way, making use of an Internet service known as the Domain Name Service or System (DNS) 11. For example, ServerA 3 with url `http://serverA.caplin.com` maps to IP address 1.1.1.1, ServerB 4 with url `http://serverB.caplin.com` maps to IP address 1.1.1.2 and ServerN 5 with url `http://serverN.caplin.com` maps to IP address 1.1.1.3. In addition a single service url maps to all of the servers in the farm 7. For example, url `http://service.caplin.com` maps to IP addresses 1.1.1.1, 1.1.1.2 and 1.1.1.3.

Referring to Figure 2, the servers 3 – 5 communicate with one another via the point to point connections 8 - 10 and update one another in real-time on the number of users each has connected. Therefore, each server machine 3 – 5 is aware of the identity and status of all of the other server machines in the farm 7. The status information held by each of the server machines 3 – 5 includes information as to whether the machine is available, for example whether it is currently 'UP', or 'DOWN', for example for maintenance. Each server machine 3 – 5 can, for example, set another server machine's status as DOWN if it fails to receive a status report when expected or following a simple negotiation to establish if the machine is available. In general terms, each server machine holds the following four pieces of information about each of the available server machines:

1. Domain Name
2. Status
3. Number of Connected Users
4. Priority

The PRIORITY field is used to allow the server farm 7 to consist of primary and secondary servers. For example, primary servers might be on a high bandwidth network and secondary servers on a low bandwidth one. The client 1 would try and connect first to the highest priority servers and only try the next priority down if no highest ones were available. This can be used for 2 or more levels of priority.

In the example given above, the information held by each server for servers 3 – 5 is:

http://serverA.caplin.com UP 2963 A

http://serverB.caplin.com DOWN 0 B

5 http://serverN.caplin.com UP 2979 A

The information indicates that ServerA and ServerN are available (status = UP) and are currently serving 2963 and 2979 users respectively, while ServerB is not currently available (status = DOWN). ServerA and ServerN both have the highest
10 level of priority (A) while ServerB has the next level down (B).

A method of load balancing across the server farm 7 will now be described in detail.

Referring to Figures 1 and 3, the client 1 requests a service by entering the service
15 url, for example service.caplin.com, at his browser (step s1). The request is sent through the Internet to the DNS system 11 for translation of the service url into a physical IP address. The DNS system 11 determines that the service url translates into N physical IP addresses (step s2). It therefore applies a round-robin algorithm, local direction or other conventional technique to route the client request to one of
20 the plurality of data servers ServerA 3, ServerB 4 and ServerN 5 (step s3). For example, the round robin DNS technique selects a first one of the N physical IP addresses, connects the user to this address and sends the selected address to the back of the list, so that a subsequent request to the DNS system 11 will be directed to a second different one of the IP addresses.

25

In this example, the service being provided is a real-time data streaming service and each of the servers 3 – 5 is a push data server implementing the RTTP (Real-Time Transfer Protocol) server-push protocol developed by Caplin Systems Ltd. To implement the data streaming service, a persistent connection, also known as a
30 'sticky' connection, is required. A connection is opened between the client and a selected server but is not closed once a response has been received from the server. Instead, the connection is maintained so that the server can send down real-time streaming data on a continuous basis, without the overhead of opening and closing

the connection each time. In this case, it is therefore important that the client 1 maintains a connection with a given server for as long as possible.

For the purpose of this example, it is assumed that the client request is routed to and received by the data server ServerN 5 (step s4). As described above with reference to Figures 1 and 2, each of the data servers 3 – 5 maintain a list of all of the data servers 3 – 5 which are capable of providing the service to the client 1. Data server ServerN 5, which therefore acts as a list server in this example, sends the list to the client 1 (step s5). The list may be in text, Javascript™, XML format or any other format which is appropriate for the particular client. The client 1 receives the list (step s6) and selects the data server from which it wishes to receive the service (step s7), based on the status and priority information for each of the data servers 3 – 5 in the list and its own predetermined rules. For example, the data server to be used is selected at random from data servers which have status 'UP' within a given priority group, with a weighting which depends on the number of connected users. For instance, each server 3 – 5 is associated with a probability of being chosen of:

$$\frac{1 - (\text{No. of connected users for selected server} / \text{Total number of connected users})}{\text{Number of live servers} - 1}$$

Therefore, for the example figures given above, the probabilities of being chosen associated with ServerA 3 is 0.501, while that for ServerC 5 is 0.499. So ServerA 3 would, in this instance, be more likely to be chosen for further communication.

Assuming ServerA 3 is chosen, the client 1 then attempts to establish a connection with ServerA 3 (steps s8, s9).

Referring to Figure 4, in the event that a connection cannot be established, or a connection that has been established subsequently fails (step s10), the client 1 attempts to reconnect to the same server (step s11). If the reconnection attempt proves successful (step s12), then the service continues as before (step s13). If it proves unsuccessful (step s12), then the client 1 re-requests the service information

(step s1) to obtain a fresh list of available servers, since the status of many of the servers is likely to have changed since the last download.

5 In an alternative embodiment, failure to connect to a selected server (step s10) leads to an immediate re-request of the service information (step s1), as indicated by the dotted line in the Figure.

10 It will be understood by the skilled person that the embodiments described above are illustrations of the invention only and many modifications and variations are possible within the scope of the claims.

Claims

1. A method of resource management, the resource comprising a plurality of servers, each of which is capable of providing a service to a client, the method
5 comprising the steps of:
 receiving a request for the service from the client;
 in response to said request, providing the client with information identifying each of the plurality of servers; and
 selecting, at the client, one of the plurality of servers as the server to be used
10 to provide the service to the client.
2. A method according to claim 1, including the step of providing the client with information relating to the status of each of the plurality of servers.
- 15 3. A method according to claim 1 or 2, including the step of providing the client with information relating to the number of users being served by each of the plurality of servers.
4. A method according to claim 3, wherein the step of selecting a server
20 includes selecting the server in dependence on the number of users being served by each of the plurality of servers.
5. A method according to any one of the preceding claims, including the step of providing the client with information relating to a grouping to which each of the
25 plurality of servers belong.
6. A method according to claim 5, including selecting the server in dependence on the grouping.
- 30 7. A method according to any one of the preceding claims, wherein the step of selecting a server comprises randomly selecting a server.

8. A method according to any one of the preceding claims, including routing the client request to one of the plurality of servers using a DNS round-robin algorithm.

5 9. A method according to any one of the preceding claims, wherein each of the plurality of servers holds information relating to all of the servers.

10. A method according to claim 9, including the step of communicating said information between the servers in real-time.

10

11. A method according to claim 9 or 10, wherein the information includes one or more of information identifying each of the servers, status information for each of the servers, information defining the number of users connected to each of the servers and grouping information for each of the servers.

15

12. A method according to any one of the preceding claims, further comprising requesting a connection to the selected server.

13. A method according to claim 12, including, in the event that the connection
20 to the selected server fails, attempting to reconnect to the selected server.

14. A method according to claim 13, further comprising, in the event that the reconnection attempt fails, re-requesting the service to obtain the identifying information for servers configured to provide the service.

25

15. A client in a client/server system, comprising:
means for requesting a service from a server;
means for receiving information in response to said request, said information identifying each of a plurality of servers which are configured to provide the service;
30 and

means for selecting one of the plurality of servers as the server to be used to provide the service to the client.

16. A client according to claim 15, wherein the information identifying each of the plurality of servers further includes information relating to the status of each of the plurality of servers.

5 17. A client according to claim 15 or 16, wherein the information identifying each of the plurality of servers further includes information relating to the number of users being serviced by each of the plurality of servers.

10 18. A client according to claim 15, 16 or 17, wherein the information identifying each of the plurality of servers further includes information relating to a grouping to which each of the plurality of servers belongs.

19. A client according to any one of claims 15 to 18, wherein the selecting means is arranged to randomly select one of the plurality of servers.

15 20. A client according to any one of claims 15 to 19, wherein the selecting means is arranged to select one of the plurality of servers in dependence on one or more of the number of users being serviced by each of the plurality of servers, the status of each of the servers and the grouping to which each of the servers belongs.

20 21. A server in a client/server system having a plurality of servers each configured to provide a service, comprising:
means for receiving a request for the service from a client; and
means for sending information to the client in response to said request, said
25 information identifying each of the plurality of servers to the client.

22. A server according to claim 21, comprising a Real-Time Text Protocol (RTTP) server.

30 23. A client/server system having a plurality of servers each configured to provide a service to a client, comprising:
means for communicating information between the servers so that each of the plurality of servers maintains information relating to all of the servers;

means for receiving a request for the service from a client; and
means for sending server information to the client in response to said
request, said server information identifying each of the plurality of servers to the
client.

5

24. A system according to claim 23, wherein the server information further
includes information relating to the status of each of the plurality of servers.

10

25. A system according to claim 23 or 24, wherein the server information further
includes information relating to the number of users connected to each of the
plurality of servers.

26. A system according to any one of claims 23 to 25, wherein the servers
comprise RTTP servers.

15

27. A system according to any one of claim 23 to 26, wherein communication
between the servers occurs in real-time.

20




Figure 1




Figure 2

2 / 3




Figure 3




Figure 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 02/02648

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L29/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, COMPENDEX, IBM-TDB, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 003 030 A (KARUSH ARNOLD ET AL) 14 December 1999 (1999-12-14)	1,3-6, 11,12, 15,17, 18,20
Y	abstract column 7, line 49 -column 9, line 55 column 11, line 46 -column 12, line 32	2,8-10, 16,23, 25,27
Y	WO 01 13228 A (SUN MICROSYSTEMS INC) 22 February 2001 (2001-02-22) abstract page 11, line 33 -page 13, line 26 page 14, line 29 -page 15, line 33 page 16, line 28 - line 33 -/-	9,10,23, 25,27

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the International filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the International filing date but later than the priority date claimed

T later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z document member of the same patent family

Date of the actual completion of the International search

29 January 2003

Date of mailing of the International search report

05/02/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Peeters, D

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 02/02648

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 055 574 A (THOMPSON JAMES WALTER ET AL) 25 April 2000 (2000-04-25) abstract column 3, line 40 -column 4, line 64 column 6, line 61 -column 7, line 28 -----	7,19
Y	AVERSA L ET AL: "Load balancing a cluster of web servers using distributed packet rewriting" COMPUTER SCIENCE DEPARTMENT TECHNICAL REPORT, NEW YORK, NY, US, 6 January 1999 (1999-01-06), pages 1-13, XP002160191	8
A	abstract page 1 page 3 -page 5 -----	7,19
Y	US 6 327 622 B1 (LIM SWEE BOON ET AL) 4 December 2001 (2001-12-04)	2,16
A	abstract column 1, line 41 -column 2, line 38 column 4, line 57 -column 5, line 24 -----	24

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB U2/02648

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6003030	A	14-12-1999	US 5956716 A	21-09-1999
			US 6181867 B1	30-01-2001
			AU 714865 B2	13-01-2000
			AU 5152298 A	15-05-1998
			EP 0932866 A1	04-08-1999
			JP 2001502830 T	27-02-2001
			WO 9818076 A1	30-04-1998
			US 6154744 A	28-11-2000
			US 6502125 B1	31-12-2002
			US 6269394 B1	31-07-2001
			AU 716842 B2	09-03-2000
			AU 6113996 A	30-12-1996
			CA 2228607 A1	19-12-1996
			EP 0834143 A1	08-04-1998
			JP 11507456 T	29-06-1999
			WO 9641285 A1	19-12-1996
			US 6496856 B1	17-12-2002
WO 0113228	A	22-02-2001	AU 6766500 A	13-03-2001
			AU 6902300 A	13-03-2001
			EP 1210662 A2	05-06-2002
			EP 1212680 A2	12-06-2002
			WO 0113227 A2	22-02-2001
			WO 0113228 A2	22-02-2001
US 6055574	A	25-04-2000	EP 1062786 A1	27-12-2000
			JP 2002507092 T	05-03-2002
			WO 9946907 A1	16-09-1999
US 6327622	B1	04-12-2001	AU 6132399 A	27-03-2000
			EP 1116112 A1	18-07-2001
			WO 0014633 A1	16-03-2000